SIEMENS

Data sheet 6ES7231-5PA30-0XB0

SIMATIC S7-1200, Analog input, SB 1231RTD, 1 AI RTD, Pt100 and Pt1000

General information	
Product type designation	SB 1231, AI 1x16 bit RTD
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	5 mA
from backplane bus 5 V DC, typ.	20 mA
Power loss	
Power loss, typ.	0.5 W
Analog inputs	
Number of analog inputs	1; Resistance thermometer
permissible input voltage for current input (destruction limit), max.	±35 V
Technical unit for temperature measurement adjustable	Degrees Celsius/degrees Fahrenheit
Input ranges	
● Voltage	Yes
● Current	No
● Thermocouple	No
● Resistance thermometer	Yes; Platinum (Pt)
● Resistance	Yes; 150 Ω, 300 Ω, 600 Ω
Input ranges (rated values), voltages	
● -80 mV to +80 mV	
— Input resistance (-80 mV to +80 mV)	>= 10 MOhm
Input ranges (rated values), resistance thermometer	
● Pt 100	Yes
— Input resistance (Pt 100)	100 Ω
● Pt 1000	Yes
— Input resistance (Pt 1000)	1 000 Ω
● Pt 200	Yes
— Input resistance (Pt 200)	200 Ω
● Pt 500	Yes
— Input resistance (Pt 500)	500 Ω
Input ranges (rated values), resistors	
● 0 to 150 ohms	Yes
● 0 to 300 ohms	Yes
● 0 to 600 ohms	Yes
Thermocouple (TC)	
Temperature compensation	
— Parameterizable	No

Subject to change without notice
© Copyright Siemens

Analog outputs	
Number of analog outputs	0
Cable length	
● shielded, max.	100 m; shielded, twisted pair
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	15 bit; + sign
● Integration time, parameterizable	No
● Interference voltage suppression for interference frequency f1 in Hz	85 dB at 10 / 50 / 60 / 400 Hz
Errors/accuracies	
Temperature error (relative to input range), (+/-)	25 °C ±0.1%, to 55 °C ±0.2% total measurement range
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.05 %
Interference voltage suppression for f = n x (f1 +/- 1 %), f1 = interference frequency	
● Common mode interference, min.	120 dB
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes; Can be read out
Alarms	
● Diagnostic alarm	Yes
Diagnoses	
● Wire break	Yes
Diagnostics indication LED	
● for status of the inputs	Yes
● for maintenance	Yes
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
Ambient conditions	
Free fall	
● Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
● min.	-20 °C
● max.	60 °C
● horizontal installation, min.	-20 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-20 °C
● vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Air pressure acc. to IEC 60068-2-13	
● Operation, min.	795 hPa
● Operation, max.	1 080 hPa
● Storage/transport, min.	660 hPa
● Storage/transport, max.	1 080 hPa
Relative humidity	
● Operation at 25 °C without condensation, max.	95 %
Pollutant concentrations	
● SO2 at RH < 60% without condensation	S02: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free
Connection method	

Subject to change without notice
© Copyright Siemens

required front connector	Yes
Mechanics/material	
Enclosure material (front)	
● plastic	Yes
Dimensions	
Width	38 mm
Height	62 mm
Depth	21 mm
Weights	
Weight, approx.	35 g

Classifications

	Version	Classification
eClass	16	27-24-22-01
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

EG-Konf. | UKCA | Miscellaneous | Manufacturer Declaration | UL | Metrological Approval

General Product Approval				EMV	For use in hazardous locations
RCM	EAC	China RoHS	Manufacturer Declaration	RCM	ATEX

For use in hazardous locations					Maritime application
IECEx	FM	UL	Miscellaneous	CCC-Ex	ABS

Maritime application

BUREAU VERITAS | DNV | RINA | RMRS | CCS (China Classification Society)

last modified: 7/2/2025

Subject to change without notice
© Copyright Siemens

© Copyright Siemens